

7,5 - 340 HP / 0.92 - 43.75 m³/min



OPSİYONEL SEÇENEKLER

SOFT STARTER

GÜRÜLTÜ İZOLASYONU

İNVERTÖR UYGULAMA

60 Hz

 YÜKSEK VERİMLİ

 ÇEVRE DOSTU

 ERGONOMİK TASARIM

MODEL	Çalışma Basıncı bar	Serbest Hava Debisi		Motor Power		Ebatlar mm W x L x H	Ağırlık Kg.	Ses Düzeyi dB(A)***
		m ³ /min	cfm	kW	HP			
VEK 7,5	7,5	0,92	32,68	5,5	7,5	650 x 750 x 1160	185	70
	10	0,75	24,45					
	13	0,61	21,79					
VEK 10	7,5	1,25	44,70	7,5	10	650 x 750 x 1160	195	70
	10	0,99	35,00					
	13	0,75	26,84					
VEK 15	7,5	1,91	67,70	11	15	750 x 820 x 1230	252	71
	10	1,55	54,85					
	13	1,23	43,57					
VEK 20	7,5	2,68	94,90	15	20	750 x 820 x 1230	387	73
	10	2,18	77,40					
	13	1,73	61,38					
VEK 25	7,5	3,39	119,9	18,5	25	850 x 930 x 1390	420	73
	10	2,77	97,9					
	13	2,31	81,4					
VEK 30	7,5	3,96	139,7	22	30	850 x 930 x 1390	480	74
	10	3,30	116,6					
	13	2,80	99,00					
VEK 40	7,5	5,42	200,4	30	40	970 x 980 x 1545	540	74
	10	4,27	161,0					
	13	3,66	134,7					
VEK 50	7,5	6,38	225,5	37	50	970 x 980 x 1545	587	73
	10	5,45	193,6					
	13	4,69	165,8					
VEK 60	7,5	7,46	264,7	45	60	1050 x 1100 x 1590	845	75
	10	6,38	225,5					
	13	5,35	200,4					
VEK 75	7,5	9,78	346,08	55	75	1200 x 1300 x 1690	940	75
	10	8,15	290,10					
	13	6,82	244,20					
VEK 100	7,5	12,56	444,9	75	100	1700 x 1800 x 1840	1350	79
	10	10,48	370,5					
	13	8,89	313,4					
VEK 125	7,5	15,96	565,47	90	125	1700 x 1800 x 1840	1750	82
	10	13,40	475,4					
	13	11,70	414,8					
VEK 150	7,5	18,20	645,8	110	150	1700 x 1800 x 1840	1980	84
	10	15,90	562,4					
	13	13,85	490,3					
VEK 180	7,5	24,72	875,5	132	180	1800 x 2750 x 1940	2150	84
	10	21,30	755,4					
	13	17,50	620,06					
VEK 220	7,5	29,35	1048,5	160	220	2000 x 2500 x 1940	2420	86
	10	24,80	875,5					
	13	20,75	735,4					
VEK 270	7,5	37,05	1324,5	200	270	2000 x 2750 x 1980	3290	88
	10	29,66	1058,8					
	13	24,50	865,2					
VEK 340	7,5	43,75	1548	250	340	2000 x 3600 x 2000	4450	88
	10	36,72	1324,5					
	13	-----	-----					